Power Sealer

White Water-Based Acrylic Sealer for Interior Surfaces

Description: -

A high-quality interior white acrylic sealer based on acrylic copolymer resin and specially modified additives, making it an ideal primer for porous surfaces and a suitable undercoat for subsequent water-based paints.

Usage: -

- **For interior use on new or previously prepared surfaces such as walls, concrete, brick, gypsum, and cement surfaces.**
- **Used as a primary sealer for walls and ceilings.**
- **Can be used as an undercoat for various water-based paints.**

Advantages: -

- **Excellent penetration into porous surfaces.**
- **Very good spreading rate.**
- **Strong adhesion to different surfaces.**
- **Enhances the adhesion of subsequent water-based paints.**

- Easy to apply and use.

Characteristics: At 25°

color	White
Density kg/liter	1.32 ± 0.05
Viscosity	120 ± 10 Krebs
Finish	Matte
Flash Point	nonflammable
Initial setting time at 25°C and 50% relative humidity	Minimum 45 Minutes
Final setting time at 25°C and 50% relative humidity	Minimum 3 – 4 hours
Second coat at 25°C and 50% relative humidity	Minimum 5 - 6 hours
Rate of use	11 - 14 m^2 per liter for one coat, depends on the nature of the surface, the thickness of the face, the method of surface preparation and the method of application.

Application instructions: -

- The surface to be painted must be clean, dry, free of dust, grease, oils, and any materials that may affect the quality of the paint and application.
- Any cracks or roughness on the surface should be treated, followed by thorough sanding and cleaning before application.
- Apply one coat of Power Sealer (one or two coats, depending on the surface condition).

- Apply 2 coats of Power X finishing products as required.
- For previously painted (old) surfaces, clean the surfaces, remove dust and debris, and sand, particularly on oily surfaces, to properly prepare the surface.
- Shake/stir the container well before use.

Safety precautions: -

- The product should be applied in a well-ventilated area.
- Gloves, protective clothing, and eye goggles should be worn during application.
- Never eat, drink, or smoke during application.
- In case of skin contamination, wash the contaminated area with water and soap.
- In case of eye contamination, immediately wash with abundant lukewarm water and consult a doctor immediately.
- Avoid spilling residues of the product into any watercourse or soil.
- The used tools should be washed immediately after completion with water.
- Dispose of product residues or empty containers according to local environmental regulations.

Dilution Rate: 15 to 25 % of the product's weight.

Application Tools: Roller, brush, spray gun.

Packages: -

The product is available in the following sizes: 2.5-liter gallon, 9-liter bucket, and 14-liter bucket.

Storage: -

The product should be stored for two years in tightly sealed containers and under appropriate storage conditions.

For more information or inquiries, Visit our website.

Power-cp.net

Disclaimer: The technical data provided herein is accurate and correct as of the publication date and is subject to change without prior notice. The information in this datasheet is not exhaustive. Application conditions should comply with those mentioned in this datasheet. The company is not responsible for any losses resulting from application under differing conditions.

Edition: 7/2025